



中国国家强制性产品认证证书

证书编号: 2024010305681639

认证委托人名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产者名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产企业名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

产品名称和系列、型号、规格

按钮开关

NF25; Uimp:6kV; Ui:600V; Ith:10A; AC-15: Ue/Ie:250V/6A、125V/10A, DC-13: Ue/Ie:24V/6A; 使用类别:AC-15, DC-13; 安装孔径: ϕ 25mm; IP54(W 型), IP40(无 W 型); 型号解释详见附页

产品标准和技术要求

GB/T 14048.5-2017

上述产品符合《强制性产品认证实施规则 低压电器 低压元器件》
(CNCA-C03-02:2024) 的要求, 特发此证。

发证日期: 2024 年 09 月 02 日 有效期至: 2029 年 09 月 01 日

证书信息和有效性可扫描下方二维码或登录发证机构网站查验,
也可在认监委网站 (www.cnca.gov.cn) 查询。



签发:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司





中国国家强制性产品认证证书

证书编号: 2024010305681639

证书附页: 第 1 页 共 1 页

NF	25	<input type="checkbox"/>	<input type="checkbox"/>	—	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	①	②	③		④	⑤	⑥	⑦	⑧	⑨

① Mounting hole 安装孔径: $\Phi 25$

② Guard Type 防护材料类型 G: Plastic Guard type, Blank : Aluminum Guard type

③ W : 防护等级 IP54, Blank: 防护等级 P40

④ Product Type 产品类型: P(Pushbutton switch), B(Illuminated Push Button Switch),
S(Selector Switch), K(Key Selector Switch)

⑤ Operation System 操作系统:
M(Push Button), A(Push Lock & Push Reset), EM(Mushroom Headed Push Button, Momentary),
EA(Mushroom Headed Push Button, Alternate), ER(Push Button, Turn to Reset);
2(3 Positions Manual Selector Switch), 3(3 Positions Manual Selector Switch),
A2(2 Positions Auto Selector Switch), A3(3 Positions Auto Selector Switch),
3R(3 Positions Left Lock & Right Auto Return Selector Switch)

⑥ Input Voltage 指示灯输入电压:
1A (AC110V 50/60Hz), 2A(AC220V 50/60Hz), 1C[AC(50/60Hz)/DC 6V], 2C[AC(50/60Hz)/DC 12V],
3C[AC(50/60Hz)/DC 24V]

⑦ Button Color 按钮颜色:
R(Red), G(Green), Y(Yellow), W(White), B(Blue), O(Orange)

⑧ Contact Block 常开触点数量:
1(Normally Open (NO) contact 1 Each), 2(Normally Open (NO) contact 2 Each)

⑨ Contact Block 常闭触点数量:
1(Normally Closed (NC) contact 1 Each), 2(Normally Closed (NC) contact 2 Each)

注: ④⑤⑥项内容可不在铭牌上标识仅在包装箱上标识。

本页为证书附页, 应与证书主页同时使用。



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2024010305681639

NAME AND ADDRESS OF THE APPLICANT

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

NAME AND ADDRESS OF THE MANUFACTURER

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

NAME AND LOCATION OF THE FACTORY

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

PRODUCT NAME,MODEL AND SPECIFICATION

Push-button Switch

NF25 ; Uimp:6kV ; Ui:600V ; Ith:10A ; AC-15 : Ue/Ie:250V/6A、125V/10A , DC-13 : Ue/Ie:24V/6A ;
AC-15 , DC-13 ; ϕ 25mm ; IP54(W) , IP40(Non- W);See the Appendix

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB/T 14048.5-2017

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C03-02:2024).

Valid from: Sep.02,2024

Valid until: Sep.01,2029

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2024010305681639

Appendix: Page 1 of 1

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

NF 25 ☐ ☐ — ☐ ☐ ☐ ☐ ☐ ☐
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① Mounting hole 安装孔径: $\Phi 25$

② Guard Type 防护材料类型 G: Plastic Guard type, Blank : Aluminum Guard type

③ W : 防护等级 IP54, Blank: 防护等级 P40

④ Product Type 产品类型: P(Pushbutton switch), B(Illuminated Push Button Switch),
S(Selector Switch), K(Key Selector Switch)

⑤ Operation System 操作系统:

M(Push Button), A(Push Lock & Push Reset), EM(Mushroom Headed Push Button, Momentary),
EA(Mushroom Headed Push Button, Alternate), ER(Push Button, Turn to Reset);
2(3 Positions Manual Selector Switch), 3(3 Positions Manual Selector Switch),
A2(2 Positions Auto Selector Switch), A3(3 Positions Auto Selector Switch),
3R(3 Positions Left Lock & Right Auto Return Selector Switch)

⑥ Input Voltage 指示灯输入电压:

1A(AC110V 50/60Hz), 2A(AC220V 50/60Hz), 1C[AC(50/60Hz)/DC 6V], 2C[AC(50/60Hz)/DC 12V],
3C[AC(50/60Hz)/DC 24V]

⑦ Button Color 按钮颜色:

R(Red), G(Green), Y(Yellow), W(White), B(Blue), O(Orange)

⑧ Contact Block 常开触点数量:

1(Normally Open (NO) contact 1 Each), 2(Normally Open (NO) contact 2 Each)

⑨ Contact Block 常闭触点数量:

1(Normally Closed (NC) contact 1 Each), 2(Normally Closed (NC) contact 2 Each)

注: ④⑤⑥项内容可不在铭牌上标识仅在包装箱上标识。

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.