



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2024010305681653

NAME AND ADDRESS OF THE APPLICANT

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

NAME AND ADDRESS OF THE MANUFACTURER

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

NAME AND LOCATION OF THE FACTORY

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

PRODUCT NAME,MODEL AND SPECIFICATION

Push-button Switch

KBL25,KSL25,KPB25 ; Uimp:1.5kV ; Ui:AC500V ; Ith=10A ; AC-15 : Ue/Ie:AC250V/6A ;
AC125V/10A ; Φ25 ; IP65(Type W),IP40(Execpt Type W) ; See the Appendix

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB/T 14048.5-2017

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C03-02:2024).

Valid from: Oct.30,2025

Valid until: Sep.01,2029

Date of original issued: Sep.02,2024

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2024010305681653

Appendix : Page 1 of 3

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

3.3 型号的解释:

1. 控制按钮开关

KPB	☐	☐	☐	-	☐	☐	☐
	1	2	3		4	5	6

① Mounting hole 25: $\Phi 25$

② -:IP40; W:IP65

③ M:momentary pushbutton switch

MS:2 step selectable pushbutton switch(1step:push function/2step:push function)

ML:2step selectable pushbutton switch(1step:push function/2step:push function)

AT: alternate pushbutton switch

EM: mushroom headed momentary pushbutton switch

EA: mushroom headed momentary pushbutton switch

ER: push look & turn reset pushbutton switch

EP: push look & turn reset pushbutton switch

④ R: red; G:green; Y:yellow; O:orange; W:white; B:blue;

⑤ number of NO contacts

⑥ number of NC contacts

注：④，⑤，⑥项内容不可再铭牌上标识，仅在包装箱上标识。

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2024010305681653

Appendix : Page 2 of 3

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

2. 指示按钮开关

KBL	☐	☐	☐	-	☐	☐	☐	☐	☐
	1	2	3		4	5	6	7	8

① Mounting hole 25: $\Phi 25$

② -:IP40; W:IP65;

③ M:momentary pushbutton switch

MS:2 step selectable pushbutton switch(1step:push function/2step:push function)

ML:2step selectable pushbutton switch(1step:push function/2step:push function)

AT: alternate pushbutton switch | EM: mushroom headed momentary pushbutton switch

EA: mushroom headed momentary pushbutton switch

ER: push lock & turn reset pushbutton switch

EP: push lock & turn reset pushbutton switch

MP:momentary pushbutton switch with protective ring

AP:alternate pushbutton switch with protective ring

④ - : filament lamp; L:LED lamp

⑤ Input voltage : 1A:AC 110V 50/60Hz;

2A:AC 220V 50/60Hz;

3A:AC 230V 50/60Hz;

1C:6V(LED lamp) or 6.3(filament lamp)AC/DC;

2C:12V AC/DC;

3C:24V AC/DC;

⑥ R: red; G:green; Y:yellow; **O:orange;** W:white; B:blue;

⑦ Number of NO contacts

⑧ Number of NC contacts

注：④，⑤，⑥项内容不可再铭牌上标识，仅在包装箱上标识。

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2024010305681653

Appendix : Page 3 of 3

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

3. 选择按钮开关

KSL	☐	☐	☐	-	☐	☐	☐	☐	☐
	1	2	3		4	5	6	7	8

① Mounting hole 25: $\Phi 25$

② -: IP40 | W: IP65

③ S2: 2 step manual return short lever

S3: 3 step manual return short lever

L2: 2 step manual return long lever

L3: 3 step manual return long lever

AS2: 2 step auto-return short lever

AS3: 3 step auto-return short lever

RS3: 3 step left-manual, right-auto-return short lever

AL2: 2 step auto-return long lever

AL3: 3 step auto-return long lever

RL3: 3 step left-manual, right-auto-return long lever

K2: 2 step manual-return key switch

K3: 3 step manual-return key switch

AK2: 2 step auto-return key switch

AK3: 3 step auto-return key switch

RK3: 3 step left-manual, right-auto-return key switch

④ -: no illumination; L: LED lamp

⑤ input voltage 1A: AC 110V 50/60Hz;

2A: AC 220V 50/60Hz;

3A: AC 230V 50/60Hz;

1C: 6V AC/DC;

2C: 12V AC/DC;

3C: 24V AC/DC;

⑥ R: red; G: green; Y: yellow; W: white; B: blue; O: orange;

⑦ number of NO contacts;

⑧ number of NC contacts;

注: ⑥、⑦、⑧项内容可不在铭牌上标识, 仅在包装箱上标识。

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.



中国国家强制性产品认证证书

证书编号: 2024010305681653

认证委托人名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产者名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产企业名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

产品名称和系列、型号、规格

按钮开关

KBL25,KSL25,KPB25; Uimp:1.5kV; Ui:AC500V; Ith=10A; AC-15:
Ue/Ie:AC250V/6A; AC125V/10A; Φ 25; IP65(W 型), IP40(无 W 型); 型号解释
详见附页

产品标准和技术要求

GB/T 14048.5-2017

上述产品符合《强制性产品认证实施规则 低压电器 低压元器件》
(CNCA-C03-02:2024) 的要求, 特发此证。

发证日期: 2025 年 10 月 30 日 有效期至: 2029 年 09 月 01 日

本证书为变更证书, 证书首次颁发日期: 2024 年 09 月 02 日
证书信息和有效性可扫描下方二维码或登录发证机构网站查验,
也可在认监委网站 (www.cnca.gov.cn) 查询。



签发:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司





中国国家强制性产品认证证书

证书编号：2024010305681653

证书附页：第 1 页 共 3 页

3.3 型号的解释：

1. 控制按钮开关

KPB	☐	☐	☐	-	☐	☐	☐
	1	2	3		4	5	6

① Mounting hole 25: $\Phi 25$

② -:IP40; W:IP65

③ M:momentary pushbutton switch

MS:2 step selectable pushbutton switch(1step:push function/2step:push function)

ML:2step selectable pushbutton switch(1step:push function/2step:push function)

AT: alternate pushbutton switch

EM: mushroom headed momentary pushbutton switch

EA: mushroom headed momentary pushbutton switch

ER: push lock & turn reset pushbutton switch

EP: push lock & turn reset pushbutton switch

④ R: red; G:green; Y:yellow; O:orange; W:white; B:blue;

⑤ number of NO contacts

⑥ number of NC contacts

注：④，⑤，⑥项内容不可再铭牌上标识，仅在包装箱上标识。

本页为证书附页，应与证书主页同时使用。



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司



中国国家强制性产品认证证书

证书编号: 2024010305681653

证书附页: 第 2 页 共 3 页

2. 指示按钮开关

KBL	☐	☐	☐	-	☐	☐	☐	☐	☐
	1	2	3		4	5	6	7	8

① Mounting hole 25: $\Phi 25$

② -:IP40; W:IP65;

③ M:momentary pushbutton switch

MS:2 step selectable pushbutton switch(1step:push function/2step:push function)

ML:2step selectable pushbutton switch(1step:push function/2step:push function)

AT: alternate pushbutton switch | EM: mushroom headed momentary pushbutton switch

EA: mushroom headed momentary pushbutton switch

ER: push lock & turn reset pushbutton switch

EP: push lock & turn reset pushbutton switch

MP:momentary pushbutton switch with protective ring

AP:alternate pushbutton switch with protective ring

④ - : filament lamp; L:LED lamp

⑤ Input voltage : 1A:AC 110V 50/60Hz;

2A:AC 220V 50/60Hz;

3A:AC 230V 50/60Hz;

1C:6V(LED lamp) or 6.3(filament lamp)AC/DC;

2C:12V AC/DC;

3C:24V AC/DC;

⑥ R: red; G:green; Y:yellow; **O:orange;** W:white; B:blue;

⑦ Number of NO contacts

⑧ Number of NC contacts

注: ④, ⑤, ⑥项内容不可再铭牌上标识, 仅在包装箱上标识。

本页为证书附页, 应与证书主页同时使用。



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司



中国国家强制性产品认证证书

证书编号: 2024010305681653

证书附页: 第 3 页 共 3 页

3. 选择按钮开关

KSL	☐	☐	☐	-	☐	☐	☐	☐	☐
	1	2	3		4	5	6	7	8

① Mounting hole 25: $\Phi 25$

② -: IP40 | W: IP65

③ S2: 2 step manual return short lever

S3: 3 step manual return short lever

L2: 2 step manual return long lever

L3: 3 step manual return long lever

AS2: 2 step auto-return short lever

AS3: 3 step auto-return short lever

RS3: 3 step left-manual, right-auto-return short lever

AL2: 2 step auto-return long lever

AL3: 3 step auto-return long lever

RL3: 3 step left-manual, right-auto-return long lever

K2: 2 step manual-return key switch

K3: 3 step manual-return key switch

AK2: 2 step auto-return key switch

AK3: 3 step auto-return key switch

RK3: 3 step left-manual, right-auto-return key switch

④ -: no illumination; L: LED lamp

⑤ input voltage 1A: AC 110V 50/60Hz;

2A: AC 220V 50/60Hz;

3A: AC 230V 50/60Hz;

1C: 6V AC/DC;

2C: 12V AC/DC;

3C: 24V AC/DC;

⑥ R: red; G: green; Y: yellow; W: white; B: blue; O: orange;

⑦ number of NO contacts;

⑧ number of NC contacts;

注: ⑥、⑦、⑧项内容可不在铭牌上标识, 仅在包装箱上标识。

本页为证书附页, 应与证书主页同时使用。



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司