



中国国家强制性产品认证证书

证书编号: 2015010305778888

委托人名称、地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产者(制造商)名称、地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产企业名称、地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

产品名称和系列、规格、型号

按钮开关

NF25; Uimp:6kV; Ui:600V; Ith:10A; AC-15: Ue/le:250V/6A、125V/10A, DC-13: Ue/le:24V/6A;
使用类别:AC-15, DC-13; 安装孔径: φ25mm; IP54(W型), IP40(无W型); 型号解
释详见附件

产品标准和技术要求

GB/T14048.5-2017

上述产品符合强制性产品认证实施规则 CNCA-C03-02:2014 的要求,
特发此证。

发证日期: 2019年05月28日 有效期至: 2020年06月02日

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书为变更证书, 证书首次颁发日期: 2015年06月02日

本证书的相关信息可通过国家认监委网站 www.cnca.gov.cn 查询



主任: 陆梅



中国质量认证中心



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2015010305778888

NAME AND ADDRESS OF THE APPLICANT

KUN HUNG ELECTRIC CO.,LTD.
(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

NAME AND ADDRESS OF THE MANUFACTURER

KUN HUNG ELECTRIC CO.,LTD.
(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

NAME AND ADDRESS OF THE FACTORY

KUN HUNG ELECTRIC CO.,LTD.
(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

PRODUCT NAME, MODEL AND SPECIFICATION

Push-button Switch

NF25; Uimp:6kV; Ui:600V; Ith:10A; AC-15; Ue/Ie:250V/6A、125V/10A, DC-13; Ue/Ie: 24V/6A; AC-15, DC-13; φ25mm; IP54(W), IP40(Non- W);See the Appendix

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB/T14048.5-2017

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO.CNCA-C03-02:2014).

Valid from: May.28,2019

Valid until: Jun.02,2020

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jun.02,2015

The certificate information is available through CNCA's website: www.cnca.gov.cn



President:

Lu Mei



CHINA QUALITY CERTIFICATION CENTRE



中国国家强制性产品认证证书

附 录

第 1 页 共 1 页

证书编号: 2015010305778888

纸 号: 2218966

型号解释:

NF	25	□	□	—	□	□	□	□	□	□
	①	②	③		④	⑤	⑥	⑦	⑧	⑨

① Mounting hole 安装孔径: $\Phi 25$

② Guard Type 防护材料类型 G: Plastic Guard type, Blank : Aluminum Guard type

③ W : 防护等级 IP54, Blank: 防护等级 P40

④ Product Type 产品类型: P(Pushbutton switch), B(Illuminated Push Button Switch), S(Selector Switch), K(Key Selector Switch)

⑤ Operation System 操作系统:

M(Push Button), A(Push Lock & Push Reset), EM(Mushroom Headed Push Button, Momentary), EA(Mushroom Headed Push Button, Alternate), ER(Push Button, Turn to Reset);
2(3 Positions Manual Selector Switch), 3(3 Positions Manual Selector Switch),
A2(2 Positions Auto Selector Switch), A3(3 Positions Auto Selector Switch),
3R(3 Positions Left Lock & Right Auto Return Selector Switch)

⑥ Input Voltage 指示灯输入电压:

1A (AC110V 50/60Hz), 2A(AC220V 50/60Hz), 1C[AC(50/60Hz)/DC 6V], 2C[AC(50/60Hz)/DC 12V],
3C[AC(50/60Hz)/DC 24V]

⑦ Button Color 按钮颜色:

R(Red), G(Green), Y(Yellow), W(White), B(Blue), O(Orange)

⑧ Contact Block 常开触点数量:

1(Normally Open (NO) contact 1 Each), 2(Normally Open (NO) contact 2 Each)

⑨ Contact Block 常闭触点数量:

1(Normally Closed (NC) contact 1 Each), 2(Normally Closed (NC) contact 2 Each)

注: ④⑤⑥项内容可不在于铭牌上标识仅在包装箱上标识。

注: 此附录与证书同时使用时有效。



主 任:

陆 楠



中国质量认证中心