



EC-Attestation of Conformity

No. N8 07 11 54505 041

Model(s):

- KH - 2204 a ER - b x y z**
- a. Lamp type**
Blank: Incandescent lamp
L: LED lamp
- b. Input voltage of lamp**
1A: 110 V a.c.; 50/60 Hz
2A: 220 V a.c.; 50/60 Hz
3A: 230 V a.c.; 50/60 Hz
- x. Number of NO contacts**
1 to 4: SPDT - NO
- y. Number of NC contacts**
1 to 4: DPDT - NC
- z. Lamp cap color**
R: Red
G: Green
Y: Yellow
O: Orange
W: White
B: Blue

Parameters:

- Rated input voltage: 125/250 V a.c.
- Rated input current: 10 A/ 6 A
- Rated insulation voltage: 250 V a.c./d.c
- Rated impulse withstand voltage: 4 kV
- Utilization category: AC-15
- Degree of protection: IP50
- Pollution degree: 3
- Overvoltage category: III
- Number of operating cycles: 100000 (electrical)
1000000 (mechanical)
- Rated Conditional Short-circuit current: 1 KA
- Remark:
When installing/inserting the equipment all requirements of the mentioned test standards must be fulfilled.

Tested according to:

- EN 60947-1:2004
- EN 60947-5-1:2004
- EN 60947-5-5:2005
- EN 60825-1:2001